

### PL MIXING WHITE

It is a phthalate free printing base used to achieve elastic and soft touching white opaque effect in textile printing.

#### Highlights

- ▶ It has elastic and white cover effect.
- ▶ It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- ▶ It use for making colors with plastisol pigments.
- ▶ At the same time pigment able to add into mixing base and obtained plastisol colors.
- ▶ It provides dropped and non-slipped property to sock base.

#### Printing Tips

- ▶ It has been manufactured for obtain to opaque cover white effect.

#### Compliance

- ▶ It is not suitable to ecological standards due to containing PVC.

#### Precautions

- ▶ It use for making colors with plastisol pigments.
- ▶ After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ▶ It is packed in 5kg,10kg and 20kg plastic cans.
- ▶ It can be mixed with PL pigments and PL White in any ratio.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: [info@inknovators.com](mailto:info@inknovators.com)

#### Mesh

Counts: 43-120 mesh



#### Squeegee

Durometer: 60-80 Shore  
V type dr. blade



#### Cure Temperatures

320°F(160°C) for 1.5 minutes



#### Additives

Do not use any additives  
that are not advised



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Clean Up

Synthetic Thinner or  
Plastisol Screen Opener



#### Health & Safety

Please see: Safety Data Sheet

